



Decorators Caulk 380ml **Technical Data Sheet**

Description

Bartoline Flexible Filler/Decorators Caulk is a flexible acrylic filler and sealant that is easy to apply, dries quickly and can be over painted with emulsion paint after 1 to 2 hours. Conforms to the harmonised European standard EN 15651-1 for façade interior applications.

Applications

Bartoline Flexible Filler/Decorator's Caulk has been specially developed for sealing interior gaps or cracks where movement can occur such as between plaster work, window frames, doorframes, skirting boards, architraves etc. Use prior to painting or papering to prevent unsightly cracks developing at a later stage.

Directions

Surfaces must be clean and dust free. Cut the tip of the cartridge, taking care not to damage the thread. Apply nozzle and cut cleanly at an angle of 45° with an opening slightly larger than the gap to be sealed. Apply using a cartridge gun. Best results will be obtained by keeping an even pressure on the gun trigger and keeping the gun at a constant angle to the surface being sealed. Smooth down within 20 minutes of application using a wetted spatula. Care should be taken at this point not to saturate the surface as this will delay drying. Any excess filler can be removed using a damp cloth. Clean tools with water. Store any unused filler in a cool, frost free place.

Health and Safety

See MSDS for full information.

Technical Data

Form	Ready to use thixotropic paste
Specific Gravity	1.62 – 1.70
Elongation at Break (%)	>100% to ISO8339
Hardness (Shore A)	Approximately 50
Tack Free Time	15 to 60 mins, dependent on thickness, ambient temperature and humidity
Full Cure	3 to 5 days, dependent on thickness, ambient temperature and humidity
Solids Content	80-84%
Slump Resistance	No slump to ISO 7390
Application Temp. Range	+4°C to +40°C
Service Temp. Range	-15°C to +75°C
Movement Accommodation	Low to medium (+/- 5%)

Packing Specification

<u>Colour</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
White	52760010	5010789760014	05010789760021	12	84	1008	28	3
Magnolia	52760040	5010789760045	05010789760052	12	84	1008	28	3
Brown	52760030	5010789760038	05010789760045	12	84	1008	28	3

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes