



## Barbecue Lighting Fluid Technical Data Sheet

### Description

Bartoline Barbecue Lighting Fluid is a quick, simple, safe and effective way to ignite traditional charcoal barbecues.

### Directions

1. Read label before use.
2. Pour charcoal into barbecue.
3. Hold the base of the container firmly and remove bottle cap by pushing down and turning anticlockwise.
4. Tilt the bottle forward towards the grill and gently squeeze bottle so that lighting fluid evenly covers charcoal.
5. NEVER SPRAY THE LIGHTING FLUID ONTO LIT COALS.
6. Replace cap immediately and store the container in a safe place away from barbecue.
7. Allow time (approx. 30 seconds) for firelighter to soak in.
8. Using a long match or piece of paper ignite the lighting fluid.
9. The charcoal will ignite and burn for a short time.
10. Wait until flames have died down and ensure that the lighting fluid is completely burned and the charcoal has ashed over before placing food on the barbecue grill.

### Health and Safety

See MSDS for full information.

### Technical Data

Measurement	Value	Test Method
Physical State	Liquid	Visual
Colour	Clear colourless	Visual
Odour	Slight hydrocarbon type	
Boiling Point	190 - 280°C	ASTM D 86
Flash point	72 - 80°C	IP170
Density	800 - 835 kg/m <sup>3</sup>	ASTM D 4052

### Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
1 Litre	15145370	5010789145378	05010789145385	12	70	840	14	5

**Customs Tariff Code**

2710 1929

**Shipping Classification**

Non-hazardous for Shipping Purposes