



Bartoline Fast Drying Wood Glue **Technical Data Sheet**

Description

Bartoline Ready-To-Use Wood Glue is a high performance water-resistant adhesive that gives rapid development of bond strength. The glue dries clear, exhibits excellent resistance to 'creep', and can be used in areas of high humidity, or where short-term water contact occurs, such as kitchens and bathrooms. It is suitable for all types of wood, including MDF and chipboard. Bartoline Ready-To-Use Wood Adhesive meets the requirements of Category D3 of EN 204 and BS 14256 Sustained Load requirements.

Directions

Surfaces should be dry and free from dust or grease. Cut spout to the required aperture. Apply the glue evenly to one surface only. Assemble the joint before the glue dries using firm hand pressure. Clamps may be used for larger joints, if required. Remove excess glue immediately with a damp cloth. Bonding will take place rapidly but allow 24 hours to achieve maximum bond strength.

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Liquid	Visual
Colour	White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity	7000 – 15000cps	Brookfield RTV 5/20
Specific Gravity	1.0 - 1.2	
pH	2.0 – 4.0	

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
125ml Bottle	58500550	5010789500559	05010789190088	12	240	2880	30	8
250ml Bottle	58500560	5010789500566	05010789236311	6	280	1680	56	5
500ml Bottle	58500570	5010789500573	05010789304966	6	140	840	35	4

Customs Tariff Code

3506 1000

Shipping Classification

Non-Hazardous for shipping purposes