



Premium Paraffin BS 2869 C1 Technical Data Sheet

Description

Bartoline Premium Paraffin is a liquid fuel for room and greenhouse heaters.

Directions

Bartoline Premium Paraffin should be used as direct by the original heater equipment manufacturer. See instructions for use, which accompanies individual products.

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Liquid	Visual
Colour	Clear yellow	Visual
Odour	Kerosene type	
Boiling Point	160 - 265°C	ASTM D86
Flash point	43°C minimum	Abel IP170
Smoke Point	34mm	IP57
Density	0.784g/ml (typical)	ASTM D4052
Char Value	10mg/kg maximum	IP10

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
4 Litre	15135240	5010789135249	05010789135256	4	40	160	10	4

Customs Tariff Code

2710 1985

Shipping Classification

Correct Shipping Name:	Kerosene
Classification:	Class 3
UN Number:	UN 1223
Packing Group:	III
Flash Point:	43 Degrees Celsius