



# Roof & Gutter Sealant 295ml Cartridge Technical Data Sheet

#### **Description**

Bartoline Roof & Gutter Sealant has been specially developed for repairing leaks in gutters, down pipes, and flashing. It will provide a permanent water resistant and weatherproof seal.

#### **Applications**

- Fills and seals gaps/cracks in most roofing applications.
- Bonds to: concrete, roofing felt, lead, zinc, steel and masonry.
- For bedding tiles, slates and flashing into position.
- Joint sealing on gutters and down pipes.
- Sticking down loose roofing felt.
- Joint sealing between corrugated iron sheeting.

#### **Directions**

Surfaces must be sound, clean, dry and free dust/grease. Carefully cut off the tip of the cartridge and screw on the nozzle. Trim the nozzle to the required size. Using a cartridge gun, apply the sealant into the gap or joint ensuring a good solid fill. If required smooth down using a spatula or stick slightly wetted with soapy water. After application, excess sealant can be removed with a cloth dipped in Bartoline White Spirit or trimmed with a knife when dry.

#### **Health and Safety**

See MSDS for full information.

#### **Technical Data**

Form	Ready to use thixotropic paste, black in colour			
Specific Gravity	1.84			
Flashpoint	Above 61°C			
Skin Formation Time	Up to 7 days depending on ambient temperature and conditions.			
Application Temp. Range	+2°C to +40°C			
Service Temp. Range	-15°C to +75°C			
Movement	Low			
Accommodation	Low			
Compatibility	Can be used in contact with most building materials			
Limitations	Slight crazing of the surface may occur on the exposed surface in direct sunlight, the bulk of the sealant will remain pliable.			
Lillitations	Do not use in constant water immersion situations			

## **Packing Specification**

Colour	Product Code	Pack Barcode	Carton Barcode	Packs Per Carton	<u>Cartons</u> <u>Per Pallet</u>	Packs Per Pallet	<u>Ti</u>	<u>Hi</u>
Black	52790010	5010789790011	05010789790028	12	128	1536	32	4

### **Customs Tariff Code**

2715 0000

## **Shipping Classification**

Not classified as hazardous for transportation