



Ready Mixed Exterior Filler **Technical Data Sheet**

Description

Ready Mixed Exterior Filler is a ready to use filler suitable for repairing cracks, holes and gaps in exterior rendering, brick, stone, wood and most building materials. Its adhesive properties allow a wide range of applications.

Directions

Preparation: Brush out loose material and ensure surfaces to be sealed are clean, dry and dust free. Cover nail heads with an oil-based paint to prevent rusting. Moisten absorbent surfaces. Do not apply when rain is imminent or in temperatures below 5°C.

Application: Work the tube well between fingers. Remove cap and cut off tip of nozzle at a 45° angle, gently squeeze product into area to be filled and level with a filling knife or scraper. For long lasting protection the repair should be sealed with an oil-based paint or varnish. Protect the filled area from rain and water until sealed. Do not use on surfaces regularly under water.

Cleaning & Storage

Clean tools with water before filler sets hard. After use, ensure cap is firmly replaced.

PROTECT FROM FROST

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity	2800 - 3600 Poise	Lamy - MSR4

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
330g tube	52720737	5010789720735	05010789353766	6	236	1416	59	4

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes