



Plaster Skim & Repair **Technical Data Sheet**

Description

Bartoline Ready Mixed Plaster Skim & Repair is suitable for repairs on plaster and plasterboard prior to decorating. It has excellent wet adhesion making it easy to apply, will not slump on vertical surfaces and can be easily smoothed. It will cover holes up to 3mm deep but for larger cavities Bartoline Ready to Use All Purpose Filler should be used followed by Plaster Skim & Repair.

Directions

Preparation: Surfaces should be sound, dry, clean and free from damp, dust and grease. Surfaces painted with gloss should be sanded to provide a key. Nail heads in plasterboard should be knocked below the surface level and covered with an oil-based paint to prevent rusting.

Application: Apply Plaster Skim & Repair to the surface using a large brush, trowel or other suitable spreader. After the initial setting the surface can be smoothed over using a wet trowel. Alternatively, the surface can be allowed to dry thoroughly and smoothed down using fine sandpaper. When the surface is dry, it can be painted or wallpapered over. Surfaces should be sealed with a plaster sealer or sealer/PVA mix before wallpapering.

Cleaning & Storage

After use, ensure lid is firmly replaced. Clean tools with water before plaster sets hard.

PROTECT FROM FROST

Health and Safety

See MSDS for full information.

Technical Data

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity	2800 - 3300	Helipath TF/Sp10
pH	7.2 – 8.0	
Specific Gravity	1.690 – 1.790	

Packing Specification

<u>Pack Size</u>	<u>Product Code</u>	<u>Pack Barcode</u>	<u>Carton Barcode</u>	<u>Packs Per Carton</u>	<u>Cartons Per Pallet</u>	<u>Packs Per Pallet</u>	<u>Ti</u>	<u>Hi</u>
2.5L Bucket	52832502	5010789832506	N/A	N/A	N/A	168	28	6
5L Bucket	52832570	5010789832575	N/A	N/A	N/A	100	25	4

Customs Tariff Code

3214 1090

Shipping Classification

Non-Hazardous for shipping purposes