



Traditional Dark Brown Coal Tar Creosote Technical Data Sheet

Description

Bartoline Traditional Dark Brown Coal Tar Creosote is a natural and highly effective wood preservative made from a complex mixture of hydrocarbon oils containing a controlled amount of tar acids. It prevents timber from drying out and splitting, inhibits the growth of fungi and at the same time destroys insects, which might otherwise damage the wood. (Not for use on internal timbers of residential properties). **For use only by professional operators.**

Directions

Preparation

Ensure that all timbers are structurally sound, dry and free from surface growths. Care should be taken to protect valuable plants and foliage during application. Children and pets should be kept away from treated timbers until they are completely dry. Timbers previously treated with Creosote, Creosote Substitute or a solvent based wood preservative will readily accept re-treatment with Bartoline Traditional Dark Brown Coal Tar Creosote. Sealed or painted timbers must be stripped back to bare wood before coating with this product. The shade may vary from batch to batch, and it is therefore recommended that containers with the same batch number are selected to ensure shade uniformity. Alternatively, premix different batches. The final shade is dependent upon the timber being treated and the previous covering applied. The colour will fade with time. To ensure suitability it is recommended that test patches are applied before general application.

Application

Bartoline Traditional Dark Brown Coal Tar Creosote can be applied by brush, spray or dip methods. A deeper colour may be attained by applying further treatments. Apply liberally, soaking the timber to achieve best results. Always ensure that end-grain timbers are fully saturated.

Coverage

Depending upon the texture and porosity of the timber to be treated, application of a single coat of Bartoline Creosote will cover at the rate of 1 litre per 8 to 10 square meters.

After Care

Clean all tools and application equipment with Bartoline White Spirit.

Health and Safety

See MSDS for full information.

Technical Data

| Measurement | Value | Test Method |
|----------------|-----------------|-------------|
| Physical State | Liquid | Visual |
| Colour | Brown | Visual |
| Odour | Strong Aromatic | |
| Boiling Point | >200°C | |
| Flash Point | >100°C | |
| Density | 1.07 – 1.15 | |

Packing Specification

| <u>Shade</u> | <u>Pack Size</u> | <u>Product Code</u> | <u>Pack Barcode</u> | <u>Carton Barcode</u> | <u>Packs Per Carton</u> | <u>Cartons Per Pallet</u> | <u>Packs Per Pallet</u> | <u>Ti</u> | <u>Hi</u> |
|--------------|------------------|---------------------|---------------------|-----------------------|-------------------------|---------------------------|-------------------------|-----------|-----------|
| Dark | 20 Litre | 81362070 | 5010789362072 | N/A | N/A | N/A | 28 | 14 | 2 |

Customs Tariff Code

2707 9100

Shipping Classification

Correct Shipping Name: Environmentally Hazardous Substance Liquid NOS (Creosote)
Classification: Class 9
UN Number: UN 3082
Packing Group: III
Additional Information: Marine Pollutant